


Single Speed Belted Fan Motors



**Ball Bearing
Commercial Ventilation!
BF-4707 (1/3 HP)
BF-4709 (1/2 HP)**



Motors

Single Speed

Part #	HP	Volts	Amps	S.F.	RPM	Rotation	A Dim.	Bearing	Shaft
BF-4701	1/4	115	5.8	1.35	1/1725	Revers.	6.25"	Sleeve	1/2"x1.5"
BF-4706	1/3	115	7.3	1.35	1/1725	Revers.	6.25"	Sleeve	1/2"x1.5"
BF-4707	1/3	115	7.3	1.35	1/1725	Revers.	6.25"	Ball	1/2"x1.5"
BF-4708	1/2	115	9.9	1.25	1/1725	Revers.	6.75"	Sleeve	1/2"x1.5"
BF-4709	1/2	115	9.9	1.25	1/1725	Revers.	6.75"	Ball	1/2"x1.5"

Features

- 48 Frame
- 5.5" Diameter
- Open Drip Proof
- Resilient Ring & Base Included
- 60 Hz
- Ball & Sleeve Bearing
- Shaft: 1/2" x 1.5" W/ Flat
- Reversible
- Split Phase
- 45°C (113°F) Ambient
- Insulation Class B
- Thermally Protected


Cross Reference

Rotom	AO Smith	Emerson	Fasco	GE	Marathon	UE	Rotom
BF-4701	GF2024	840CV	D6002	4701, H701	D127, B206, B303	-	R840
BF-4706	GF2034	841CV	-	4706, H711	D143, B207	-	R841
BF-4707	GF2034B	2888	D6004	4682, H165	B305, B703	906, 921, 922	R2888
BF-4708	GF2054	1542C	-	4708	D162, B208	-	R5794
BF-4709	-	2887	D6006	4684, H703	B307	-	R2887

Two Speed Belted Fan



- Reversible
- Shaded Pole & Split Phase
- Resilient Ring & Base Included



Part #	HP	Volts	Amps	S.F.	RPM	Type	C Dim.	Fr.	Bearing	Shaft
R5793	1/3	115	6.7	1.35	2/1725	SPLT/ ODP	8.30"	56Z	Sleeve	1/2"x1.6"
R5794	1/2	115	7.20	1.25	2/1725	SP/ Open.	9.9"	48/56	Sleeve	1.5"x1/2"

Part #	Comment
R5793	Emerson 5793, K5793, U.E. 849, G.E. 5J765GS
R5794	B200, D149, D162, S121, 1542, 7J403AS, 7J403AX

*5/8" Thru-bolts shaft end.

Rotation determined opposite shaft end
Double shaft determined at lead end

Shaft length measured from hub
face to shaft end