


## 5.5" Direct Drive Motors

- **Less Inventory Required!**
- **Versatile!**
- **Time Saver!**
- **Easy Installations!**

Replaces:  
 Lennox 76N17  
 GE Mars 03463  
 Emerson 5460  
 Rheem-Ruud 51-23012-41



### Features


- Energy Efficient
- Different Capacitor/Speed Combos
- Designed for 370V Cap (not incl.)
- Permanent Split Capacitor
- Ball and Sleeve Bearing
- Reversible Rotation
- Resilient Rings
- Extended Thru Bolts
- Automatic Protector
- Class B Insulation
- 48 Frame
- Single Phase
- Continuous Duty-Over Air
- Mounts by Belly Band, Thru Bolts or Shell Holes
- Rheem Mounting Holes in Shell
- 60 Hz

Part #	HP	Spd.	RPM	Volt	Amps	Capacitor (370V)		Bearing	Leads	Dia	Shaft	
R43600	1/2	All	1075	115	7.0	10 mfd		Sleeve	26"	4.86"	1/2"x5"	
	1/3	All			6.7	5	mfd					7.5*
	1/4	Lo, Med-Lo, Med-Hi			4.4							
	1/5	Low, Med-Lo			3.2							
	1/6	Lo			2.4							
R43601	1/2	All	1075	208-230	3.9	10 mfd		Sleeve	26"	4.86"	1/2"x5"	
	1/3	All			3.6	5	mfd					7.5*
	1/4	Lo, Med-Lo, Med-Hi			2.5							
	1/5	Lo, Med-Lo			1.8							
	1/6	Lo			1.3							
R43602	3/4	All	1075	115	9.1	10 mfd		Ball	38"	4.86"	1/2"x5 1/2"	
	1/2	All			6.8	5	mfd					7.5*
	1/3	All			5.5							
	1/4	Lo, Med-Lo, Med-Hi			3.0							
	1/5	Lo, Med-Lo			2.3							
R43603	3/4	All	1075	208-230	3.9	10 mfd		Ball	38"	4.86"	1/2"x5 1/2"	
	1/2	All			3.6	5	mfd					7.5*
	1/3	All			3.0							
	1/4	Lo, Med-Lo, Med-Hi			2.3							
	1/5	Lo, Med-Lo			2.0							

\* Motor approximately 10% stronger & has higher starting torque for 1/6, 1/5, 1/4 & 1/3 HP rating with the 7.5 mfd 370VAC capacitor.

## Condenser Fan Multi HP

Part #	HP	Spd.	RPM	Volt	Amps	Cap. (370V)		Bearing	Leads	Dia.	Shaft	
						208V	230V					
R22601	1/3	High	825	208-230	1.9	10	mfd	7.5	Ball	36"	5.24"	1/2"x5"
	1/4				1.5							
	1/5	Low			1.2							
	1/6				1.0							
	1/2				2.4							
R22603	1/2	High	825	208-230	1.7	12.5	mfd	10	Ball	36"	5.61"	1/2"x6"
	1/3				1.4							
	1/4	Low			1.1							
	1/5				1.1							
	1/6				1.1							
R22600	1/3	High	1075	208-230	2.8	7.5	mfd	5	Sleeve	36"	4.86"	1/2"x6"
	1/4				2.0							
	1/5	Low			1.7							
	1/6				1.5							
	1/2				2.8							
R22605	1/3	High	1075	208-230	2.0	7.5	mfd	5	Ball	36"	4.86"	1/2"x6"
	1/4				2.0							
	1/5	Low			1.7							
	1/6				1.5							
	1/2				3.9							
R22602	1/2	High	1075	208-230	3.9	12.5	mfd	10	Ball	36"	5.24"	1/2"x5"
	1/3				2.2							
	1/4	Low			1.6							
	1/5				1.3							
	1/6				1.3							
R22604	3/4	High	1075	208-230	5.3	15	mfd	12.5	Ball	36"	5.87"	1/2"x6"
	1/2				3.0							
	1/3	Low			1.9							
	1/4				1.0							
	1/6				1.0							



### Features

- **LESS INVENTORY REQUIRED!**
- **VERSATILE!**
- **TIME SAVER!**
- **EASY INSTALLATIONS!**
- Totally Enclosed
- Energy Efficient
- Different Capacitor/Speed Combos
- Designed for 370V Cap (not incl.)
- Permanent Split Capacitor
- Ball and Sleeve Bearing
- Reversible Rotation
- Resilient Rings (Direct Drive)
- Extended Thru Bolts
- Automatic Protector
- Class B Insulation
- 48 Frame
- Single Phase
- Continuous Duty-Over Air
- Mounts by Belly Band, Thru Bolts or Shell Holes
- Rheem Mounting Holes in Shell
- 60 Hz

**Totally Enclosed  
 Air Over  
 60°C Ambient**